

CLAIMS

What is claimed is:

- 5  
Sub a1
1. An optical sub-assembly for processing an optical signal, the sub-assembly comprising:
    - a working path of the optical network;
    - a first sub-band of the optical signal carried only by the working path;
    - a protect path of the optical network;
    - 10 a second sub-band of the optical signal carried only by the protect path;
    - a first module disposed along the working path for affecting the working path;
    - and
    - a second module disposed along the protect path for affecting the protect path.
  - 15 2. The sub-assembly of claim 1, wherein the first sub-band is one of a C-band and an L-band, and the second sub-band is the other of a C-band and an L-band.
  3. The sub-assembly of claim 1, wherein the first and second modules are comprised of optical amplifiers.
  - 20 4. The sub-assembly of claim 1, wherein the first and second modules are comprised of band pass filters.
  5. The sub-assembly of claim 1, wherein the first and second modules are comprised of channel add devices.
  - 25 6. The sub-assembly of claim 1, wherein the first and second modules are comprised of channel drop devices.
  - 30 7. The sub-assembly of claim 1, wherein the first and second modules are comprised of demultiplexers.

T0T050" T6024860

8. The sub-assembly of claim 1, wherein the first and second modules are comprised of multiplexers.

5 9. The sub-assembly of claim 1, wherein the first and second modules are comprised of interleavers.

10. The sub-assembly of claim 1, wherein the first and second modules are comprised of attenuators.

10 11. The sub-assembly of claim 1, wherein the first and second modules are comprised of dispersion compensation modules.

12. A method of processing an optical signal in an optical network, comprising the steps of:

15        separating the optical signal into a first sub-band and a second sub-band;  
         routing the first sub-band through a first module and routing the second sub-band through a second module of the same type as the first module; and  
         recombining the first and second sub-bands.

20 13. The method of claim 12, wherein the separating step comprises the step of routing the optical signal through an LC splitter.

25 14. The method of claim 12, further comprising the step of assigning the first sub-band to one of a working path and a protect path and assigning the second sub-band to the other of the working path and protect path.

sub  
a1 } 15. The method of claim 12, wherein the routing step further comprises amplifying the first sub-band with the first module and amplifying the second sub-band with the second module.

30 16. The method of claim 12, wherein the routing step further comprises filtering the first sub-band with the first module and filtering the second sub-band with the second module.

09847091-050101

- 5
17. The method of claim 12, wherein the routing step further comprises adding at least one channel to the first sub-band with the first module and adding at least one channel to the second sub-band with the second module.
18. The method of claim 12, wherein the routing step further comprises dropping at least one channel from the first sub-band with the first module and dropping at least one channel from the second sub-band with the second module.
- 10
19. The method of claim 12, wherein the routing step further comprises demultiplexing the first sub-band with the first module and demultiplexing the second sub-band with the second module.
- 15
20. The method of claim 12, wherein the routing step further comprises multiplexing the first sub-band with the first module and multiplexing the second sub-band with the second module.
- 20
21. The method of claim 12, wherein the routing step further comprises interleaving the first sub-band with the first module and interleaving the second sub-band with the second module.
- 25
22. The method of claim 12, wherein the routing step further comprises attenuating the first sub-band with the first module and attenuating the second sub-band with the second module.
- 30
23. The method of claim 12, wherein the routing step further comprises compensating for dispersion of the first sub-band with the first module and compensating for dispersion of the second sub-band with the second module.
24. An optical amplifier node for amplifying an optical signal, the amplifier node comprising:
- a first amplifier for amplifying only signals from a first sub-band of the optical signal, wherein the signals are carried only by a working path; and

TOTO "T604860

a second amplifier for amplifying only signals from a second sub-band of the optical signal, wherein the signals are carried only by a protect path.

25. The optical amplifier node of claim 24, further comprising a sub-band splitter for  
5 splitting the optical signal into at least two sub-bands.

26. The optical amplifier node of claim 25, wherein the sub-band splitter is an L/C splitter.

10 27. The optical amplifier node of claim 24, further comprising a sub-band combiner for combining at least two sub-bands into the optical signal.

28. The optical amplifier node of claim 27, wherein the sub-band combiner is an L/C combiner.

0947091 050101  
T0T050" T6024860